

**BLAIRS
SECURED BY DESIGN
ENHANCED CASEMENT CANOPY ACTION – STANDARD SPECIFICATION**

SASH

Canopy action reversible for easy cleaning. An initial opening restrictor and reverse position catch are incorporated in the hinge mechanism

PERFORMANCE

The window is tested to B.S. 6375 and to BS 7950.

GLAZING

The glazing system is fully drained and vented. The glass rebate up-stand is 18mm. The glass rebates will accept glazing units to a recommended thickness up to 24mm overall. The glass is fixed by timber glazing beads and high security glazing tapes. The windows are only supplied factory glazed.

TIMBER

Top quality unsorted Redwood or Hardwood.

TREATMENT

All permeable timber treated to comply with BS 5589.

JOINTS

Combed joints to frames and sashes. Fixed with non-ferrous concealed fasteners.

GLUE

Conforms with BS EN 204 Group D3 or DIN 68602 B4. Water resistant PVA glue

GASKET

Full compression seals.

PAINT/STAIN

Can be supplied factory finished.

RECOMMENDED SASH SIZES

Minimum 412mm wide x 524mm high.

Maximum 1500mm wide x 1558mm high

MULTI-PANE SASHES

Finebar Pressure Bonded astragals can be specified.